



MODEL 8.140 FL/FD-MT

5 TON 4x2 FREIGHT CARRIER / TIPPER

FAW ModelSS 8.140 FL_MT Jun2021.indd 1 2022/08/23 12:59:12

4x2 FREIGHT CARRIER

①

Permissible Road Speed 100km/h

PERFORMANCE

Gradeability @ V

CAB

Cab Control Forward Tilt Cab
Seating Driver + 2 Passengers
Type/Extras Day Cab, Aircon, Radio with USB

ENGINE

Make & Model

Capacity

3 760 cm³

Layout & Type

4 cylinder in line, water cooled, turbo charged & intercooled

Emissions Standard

Euro III

105@2600

450 @ 1 200 - 2 200

Power @ r/min (kW)
Torque @ r/min (Nm)



											120	
											٦.,	
											100	
460											80	
450		_				$\overline{}$					1	Power (XV)
440							_				60	ě
£ 430	7										40	å
0430 86 420 64 410	\mathbb{Z}							$\overline{}$			20	
400									$\overline{}$			
390	$\overline{}$								$\overline{}$		7	
380									_/			
	8 9	2	9							8		
Engine Speed (RPM)												

TRANSMISSION

 Make & Model
 WLY 6G55

 Type
 6 Speed Manual Synchromesh

 Forward Ratios
 6.20, 3.29, 2.03, 1.37, 1.00, 0.78

 Reverse Ratio
 5.68

CLUTCH

Diameter 350 mm

Type Single Plate

Operation Hydraulic-Air Assisted

STEERING

Gear Ratio 17.76:1

Type Recirculating Ball

Operation Power Assisted

AXLES Front Axle Rear Axle Gearing Type Rear Axle Ratio BRAKES System Type Park/Emergency System

FUEL IANK		
Number	One	
Total Capacity	130 Litre	

Max 29%

4.33:1

I-section Beam (forged steel)

Full Floating - Single Reduction

Full Air - Dual Circuit with ABS

Spring Brakes/Rear Booster

ELECTRICAL SYSTEM

System Voltage & Type 24V Negative Earth
No. of Batteries Two X 12V

CHASSIS

Type Straight Ladder Type - Riveted
Front Suspension Semi-Elliptical Leaf Springs with
Double Acting Shock Absorbers
Semi-Elliptical Leaf Springs
with Auxillary Springs

WHEELS

 Tyre Size
 235/75 R17.5 16PR


 Rim Size
 17.5 x 6.75

 Type
 Tubeless Radial

MASS DATA	kg
Manufacturer's Gross Vehicle Mass (GVM)	8 999
Manufacturer's Gross Combination Mass (GCM)	14 000
Manufacturer's Front Axle Mass (GA Front)	3 000
Manufacturer's Rear Axle Mass (GAU Rear)	5 999
Permissible Gross Vehicle Mass (V)	8 999
Permissible Gross Combination Mass (D/T)	14 000
Permissible Front Axle Mass (A Front)	3 000
Permissible Rear Axle Mass (A Rear)	5 999
Unladen Front Axle Mass (T Front)	1 780
Unladen Rear Axle Mass (T Rear)	1 200
Unladen Mass Total (Tare)	2 980
Body and Payload Allowance	6 019

DIMENSIONS	mm
Wheelbase (WB)	3 860
Overall Length (OL)	6 810
Cab Length (A)	1 655
Overall Width (OW)	2 038
Overall Height (OH)	2 385
Front Overhang (D)	1 150
Rear Overhang (ROH)	1 800
Cab to Rear Axle (CA)	3 360
Recommended Body Length	5 100
Cab to End of Chassis (F)	5 155
Minimum Turning Radius	7 100
Minimum Turning Diameter	14 200
Ground Clearance	200
Track - Front	1 650
Track - Rear	1 540
Chassis Outer Width	795
Chassis Inner Width	645

3360mm 5160mm 1200 3860 1800



The above specifications are not binding - subject to change without prior notice.

