





MODEL 16.240 FD/FT

4x2 6m³ TIPPER & 4x2 TRUCK TRACTOR

4x2 6m³ TIPPER & 4x2 TRUCK TRACTOR MODEL 16.240 FD/F

САВ		PERFORMANCE		MASS DATA	kg
Cab Control	Forward Tilt Cab	Gradeability @ V	Max 38%	Manufacturer's Gross Vehicle Mass (GVM)	18 000
Seating	Driver + 1 Passenger	Permissible Road Speed	80km/h	Manufacturer's Gross Combination Mass (GCM)	32 000
Type/Extras	Semi Sleeper with Aircon, Radio			Manufacturer's Front Axle Mass (GA Front)	7 000
	with USB, Suspension Seat	AXLES		Manufacturer's Rear Axle Mass (GAU Rear)	11 000
ENGINE		Front Axle	I-section Beam (forged steel)	Permissible Gross Vehicle Mass (V)	16 000
Make & Model	FAW CA6DF2-24	Rear Axle -		Permissible Gross Combination Mass (D/T)	32 000
Capacity	7 127 cm ³	Gearing Type	Full Floating - Single Reduction	Permissible Front Axle Mass (A Front)	7 000
	6 cylinder in line, water cooled,	Rear Axle Ratio	4.875:1	Permissible Rear Axle Mass (A Rear)	9 000
Layout & Type	turbo charged & intercooled			Unladen Front Axle Mass (T Front)	3 560
Emissions Standard	Euro II	BRAKES		Unladen Rear Axle Mass (T Rear)	2 260
Power @ r/min (kW)	177 @ 2 300	BRAREO		Unladen Mass Total (Tare)	5 820
Torque @ r/min (Nm)	890 @ 1 400	System Type	Full Air - Dual Circuit with ABS	Body and Payload Allowance	10 180
	1000	Park/Emergency	Spring Brakes/Rear Booster		
M. T. Marin	900	System	opining Brakes/Rear Booster	DIMENSIONS	mm
	700 600			Wheelbase (WB)	3 800
	500	FUEL TANK		Overall Length (OL)	6 375
	400 Torque Nm	Number	One	Cab Length (A)	2 185
	200	Total Capacity	200 Litre	Overall Width (OW)	2 470
	800 900 1000 1200 1400 1500 1700 1900 2100 2300	Total Odpacity	200 Elite	Overall Height (OH)	2 760
		ELECTRICAL SYSTE		Front Overhang (D)	1 375
TRANSMISSION				Rear Overhang (ROH)	1 200
Make & Model	Fast Gear 8 JS 118 TC - B	System Voltage & Type	24V Negative Earth	Cab to Rear Axle (CA)	2 874
Туре	8 Speed Range Change	No. of Batteries	Two X 12V	Recommended Body Length	3 900
Forward Ratios	9.32, 6.09, 4.06, 3.10, 2.30, 1.5,			Cab to End of Chassis (F)	4 074
FOIWAIU RALIOS	1.0, 0.76	CHASSIS		Minimum Turning Radius	6 500
Reverse Ratio	9.28	Туре	Straight Ladder Type - Riveted	Minimum Turning Diameter	13 000
СLUTCH			Semi-Elliptical Leaf Springs with	Ground Clearance	220
	420	Front Suspension	Double Acting Shock Absorbers	Track - Front	2 000
Diameter	430 mm	Rear Suspension	Semi-Elliptical Leaf Springs	Track - Rear	1 847
Type	Single Plate		with Auxillary Springs	Chassis Outer Width	865
Operation	Hydraulic-Air Assisted			Chassis Inner Width	680
STEERING		WHEELS			
Gear Ratio	20.5:1	Tyre Size	11.00 R22.5 16PR		
	Recirculating Ball	Rim Size	8.25 X 22.5		
Туре	Recirculating Dali				





The above specifications are not binding - subject to change without prior notice.

